

Safety Data Sheet
acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

1 Identification

- **Product identifier**
- **Trade name:** CS6339REDM3
- **Article number:** 14197
- **Relevant identified uses of the substance or mixture.** Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Royal Adhesives & Sealants, LLC
Aerospace & Marine Inflatable Adhesives & Coatings Division
48 Burgess Place
Wayne, NJ 07470
Information Phone Number: 973-694-0845
Emergency Phone Number: 973-694-0845
- **Information department:** Environment protection department.
- **Emergency telephone number:** ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

- Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

- Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

(Contd. of page 1)

Hazard statements

- Highly flammable liquid and vapor.
- Causes skin irritation.
- Suspected of damaging fertility or the unborn child.
- May cause drowsiness or dizziness.
- May cause damage to organs through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.

Precautionary statements

- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Read label before use.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 1
Fire = 3
Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 1
Fire = 3
Physical Hazard = 0

Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Adhesive

Dangerous components:

110-54-3	n-hexane	10-25%
108-88-3	toluene	5-20%
110-82-7	cyclohexane	2.5-10%
	TSRN1397250002-5010P	na%
	TSRN1397250002-5173P	na%
	TSRN1397250002-5594P	na%
67-56-1	methanol	≤1.0%

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Wipe excess from skin.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.
- **After swallowing:**
Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, sand, extinguishing powder. Do not use water.
Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

-USA-

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Avoid prolonged or repeated contact with skin.
 - Avoid contact with eyes.
 - Wash thoroughly after handling.
 - Open containers in a well ventilated area and avoid breathing headspace vapors.
 - Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
 - Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
 - Information about storage in one common storage facility: Store away from oxidizing agents.
 - Further information about storage conditions:
 - Protect from contamination.
 - Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

110-54-3 n-hexane (10-25%)

PEL	Long-term value: 1800 mg/m ³ , 500 ppm
REL	Long-term value: 180 mg/m ³ , 50 ppm
TLV	Long-term value: 176 mg/m ³ , 50 ppm
	Skin; BEI

108-88-3 toluene (5-20%)

PEL	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm
	BEI

110-82-7 cyclohexane (2.5-10%)

PEL	Long-term value: 1050 mg/m ³ , 300 ppm
REL	Long-term value: 1050 mg/m ³ , 300 ppm
TLV	Long-term value: 344 mg/m ³ , 100 ppm

67-56-1 methanol (≤1.0%)

PEL	Long-term value: 260 mg/m ³ , 200 ppm
-----	--

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

(Contd. of page 4)

REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

• **Ingredients with biological limit values:**

110-54-3 n-hexane (10-25%)

BEI	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis
-----	---

108-88-3 toluene (5-20%)

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

67-56-1 methanol (≤1.0%)

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**

• **Personal protective equipment (see listings below)**

• **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

• **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

(Contd. of page 5)

- Material of gloves

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:

Safety glasses with side shields.



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Appearance:

Form:

Liquid

Color:

Not determined.

- Odor:

Characteristic

- Odour threshold:

Not determined.

- pH-value:

Not determined.

- Change in condition

Melting point:

Undetermined.

Boiling point:

69 °C (156 °F)

- Flash point:

-26 °C (-15 °F)

- Flammability (solid, gaseous):

Not applicable.

- Ignition temperature:

240 °C (464 °F)

- Decomposition temperature:

Not determined.

- Auto igniting:

Product is not selfigniting.

- Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- Flammable limits:

Lower:

1.2 Vol %

Upper:

7.4 Vol %

- Vapor pressure at 20 °C (68 °F):

160 hPa (120 mm Hg)

- Specific gravity at 20 °C (68 °F):

0.783 g/cm³ (6.534 lbs/gal)

- Relative density

Not determined.

- Vapour density

Not determined.

- Evaporation rate

Not determined.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

(Contd. of page 6)

- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - VOC (Per EPA 24)** not available GMS/L
- **Other information**
 - Weight Per Gallon 6.54
 - Lbs VOC/Gallon [less water. less exempts] 4.38
 - Grams/Liter [less water. less exempts] 524.89

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** not reactive, as supplied.
- **Conditions to avoid** Heat, flames, sparks.
- **Incompatible materials:**
 - Reacts with oxidizing agents.
 - Reacts with acids.
- **Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Hydrocarbons

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

110-82-7 cyclohexane

Oral	LD50	12705 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
 - **on the skin:** Skin irritant.
 - **on the eye:**
 - May irritate the eye.
 - Vapors may be irritating to the eyes.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Irritant

(Contd. on page 8)

—USA—

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

(Contd. of page 7)

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-88-3 | toluene

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

DOT, ADR, IMDG, IATA

UN1133

- **UN proper shipping name**

DOT

Adhesives

ADR

1133 Adhesives, ENVIRONMENTALLY HAZARDOUS

IMDG, IATA

ADHESIVES

(Contd. on page 9)

—USA—

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

(Contd. of page 8)

· Transport hazard class(es)

· DOT



· Class

3 Flammable liquids.

· Label

3

· ADR



· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids.

· Label

3

· Packing group

· DOT, ADR, IMDG, IATA

II

· Environmental hazards:

Product contains environmentally hazardous substances:
cyclohexane, n-hexane

· Special marking (ADR):

Symbol (fish and tree)

· Special precautions for user

Warning: Flammable liquids

· Danger code (Kemler):

33

· EMS Number:

F-E,S-D

· Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code

Not applicable.

· UN "Model Regulation":

UN1133, Adhesives, ENVIRONMENTALLY HAZARDOUS, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3

• Proposition 65

(Contd. of page 9)

• Chemicals known to cause cancer:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity:

108-88-3 toluene

67-56-1 methanol

• (DSL) Canada Domestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

• Cancerogenity categories

• EPA (Environmental Protection Agency)

110-54-3 n-hexane

108-88-3 toluene

110-82-7 cyclohexane

II

II

I

• TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene

A4

• MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• National regulations:

• Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this MSDS are presented in good faith and are believed to be correct as of the date of this MSDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the MSDS.

• Department issuing MSDS: Environment protection department.

• Creation Date: 09/11/2013

• Date of preparation / last revision 05/16/2014 / -

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

(Contd. on page 11)

USA

Safety Data Sheet
acc. to OSHA HCS

Printing Date 05/16/2014

Revision Number 1

Revision Date 05/16/2014

Trade name: CS6339REDM3*Repr. 2: Reproductive toxicity, Hazard Category 2*

(Contd. of page 10)

*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3**STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2**Asp. Tox. 1: Aspiration hazard, Hazard Category 1*

— USA —