



Section 1: Product & Company Identification

Product Name: Jump Start® Starting Fluid with Lubricity

Product Number (s): 75671

Product Use: Starting Fluid

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

1-215-674-4300(General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

www.crc-canada.ca

1-905-670-2291

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely Flammable. Harmful or Fatal if Swallowed. Vapor Harmful.
Contents Under Pressure.

Appearance & Odor: Clear liquid, ether odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause moderate eye irritation and moderate corneal injury.

SKIN: Prolonged contact may cause irritation, defatting of the skin.

INHALATION: May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

INGESTION: If aspirated into lungs, it may be rapidly absorbed through the lungs and result in injury to other body systems; gastro-intestinal distress.

CHRONIC EFFECTS: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TARGET ORGANS: Nervous system

Medical Conditions Aggravated by Exposure: Unknown

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: **Jump Start® Starting Fluid with Lubricity**

Product Number (s): **75671**

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Diethyl ether	60-29-7	20 – 25
Heptane	142-82-5	75 – 80
Carbon dioxide	124-38-9	< 10
Upper cylinder lubricant	64741-89-5	< 1

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting. Call a physician immediately.

Note to Physicians: Aspiration hazard. Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is extremely flammable in accordance with aerosol flammability definitions. (See 16 CFR 1500.3(c)(6)).

Flash Point: < 20°F / -7°C (TCC) Upper Explosive Limit: 48.0
Autoignition Temperature: ND Lower Explosive Limit: 1.2

Fire and Explosion Data:

Suitable Extinguishing Media: Carbon dioxide, foam, dry chemical, Class B extinguishers

Products of Combustion: Oxides of carbon

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate

Product Name: Jump Start® Starting Fluid with Lubricity

Product Number (s): 75671

respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not use near open flames, heat or any sources of ignition. Vapors are heavier than air and will collect in low areas. Use proper ventilation that will remove vapors from low areas. Avoid prolonged or repeated contact with skin. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing. Do not store near sources of ignition.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Diethyl ether	400	NE	400	500	NE		ppm
Heptane	500	NE	400	500	NE		ppm
Carbon dioxide	5000	NE	5000	30000	NE		ppm
Upper cylinder lubricant	NE	NE	NE	NE	NE		

N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid

Product Name: Jump Start® Starting Fluid with Lubricity**Product Number (s): 75671**

Color: clear, colorless
 Odor: ether
 Odor Threshold: ND
 Specific Gravity: 0.7
 Initial Boiling Point: 95°F / 35°C
 Freezing Point: ND
 Vapor Pressure: ND
 Vapor Density: > 1 (air = 1)
 Evaporation Rate: fast
 Solubility: slight in water
 Coefficient of water/oil distribution: ND
 pH: NA
 Volatile Organic Compounds: wt %: 97.0 g/L: 679 lbs./gal: 5.66

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition; excessive heat

Incompatible Materials: Strong oxidizers; amines; nitric plus acetic acids; nitric plus sulfuric acid

Hazardous Decomposition Products: Oxides of carbon

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Diethyl ether	1215 mg/kg	> 20 mL/kg	No data
Heptane	No data	No data	103 g/m ³ /4H
Carbon dioxide	No data	No data	470,000 ppm/30M
Upper cylinder lubricant	> 15 mg/kg	> 5 mg/kg	No data

Chronic Toxicity:

Component	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen	Irritant	Sensitizer
Diethyl ether	No	No	No	Unknown	Unknown
Heptane	No	No	No	E & R (mild) / S (moderate)	No
Carbon dioxide	No	No	No	No	Unknown
Upper cylinder lubricant	No	No	No	Unknown	Unknown

E – Eye	S – Skin	R - Respiratory
---------	----------	-----------------

Reproductive Toxicity: No information available
Teratogenicity: No information available
Mutagenicity: No information available
Synergistic Effects: No information available

Product Name: Jump Start® Starting Fluid with Lubricity

Product Number (s): 75671

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Heptane – 24 Hr EC50 Daphnia magna: > 10 mg/L

Persistence / Degradability: No information available

Bioaccumulation / Accumulation: No information available

Mobility in Environment: No information available

Section 13: Disposal Considerations

Waste Classification: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with a waste code of D001. (See 40 CFR Part 261.20 – 261.33)
Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): UN1950, Aerosols, flammable, 2.1, Limited Quantity**

ICAO/IATA (air): UN1950, Aerosols, flammable (engine starting fluid), 2.1

IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: IATA: Forbidden on passenger aircraft

**This product can be classified and labeled as 'Consumer Commodity, ORM-D' for domestic ground shipping until December 31, 2020

If shipping as limited quantity by ground, note that shipping papers are not required.

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: diethyl ether (100 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	Yes
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Product Name: Jump Start® Starting Fluid with Lubricity

Product Number (s): 75671

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Occupational Safety and Health Administration (OSHA):

This product is regulated under the Hazard Communication Standard.

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)	
Health:	2
Flammability:	4
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
CRC #: 05671
Revision Date: 07/27/2015

Changes since last revision: Removed Product Number
Section 14: Transport Information
Section 15: Regulatory Information

Product Name: Jump Start® Starting Fluid with Lubricity

Product Number (s): 75671

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists	NA: Not Applicable
CAS: Chemical Abstract Service	ND: Not Determined
CFR: Code of Federal Regulations	NIOSH: National Institute of Occupational Safety & Health
DOT: Department of Transportation	NFPA: National Fire Protection Association
DSL: Domestic Substance List	NTP: National Toxicology Program
g/L: grams per Liter	OSHA: Occupational Safety and Health Administration
HMIS: Hazardous Materials Identification System	PMCC: Pensky-Martens Closed Cup
IARC: International Agency for Research on Cancer	PPE: Personal Protection Equipment
IATA: International Air Transport Association	ppm: Parts per Million
ICAO: International Civil Aviation Organization	RoHS: Restriction of Hazardous Substances
IMDG: International Maritime Dangerous Goods	STEL: Short Term Exposure Limit
IMO: International Maritime Organization	TCC: Tag Closed Cup
lbs./gal: pounds per gallon	TWA: Time Weighted Average
LC: Lethal Concentration	WHMIS: Workplace Hazardous Materials Information System
LD: Lethal Dose	