

Version 2.

Print Date 09/17/2010

TR2103650001

REVISION DATE: 09/22/2008

SECTION 1 - PRODUCT IDENTIFICATION

Trade name

TAMOSEAL WHITE 50# BG (STD)TAMOSEAL WHITE 50# BG (STD)

Product code

: TR2103650001

COMPANY

: Euclid Chemical Company 19218 Redwood Road

Cleveland, OH 44110

Telephone

: 1-800-321-7628

Emergency Phone:

: U.S. only: 1-800-424-9300

International Users Call Collect: 1-703-527-3887

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

White. Powder. Dust may irritate nose and throat. Dust irritating to the respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation

Dust may irritate nose and throat. Dust irritating to the respiratory tract.

Eyes

Direct contact may cause severe irritation. May cause mechanical irritation or abrasion, and

possible chemical burns. May cause temporary injury

Ingestion

May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation,

nausea, and vomiting.

Skin

An RPM Company

May cause severe irritation. May cause dryness, cracking, irritation, and chemical burns

May produce cement dermatitis due to primary irritation from alkaline, hydroscopic and

abrasive properties

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
Portland cement	65997-15-1	40.0 - 70.0	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	30.0 - 60.0	
Stabilizer	NJ TSRN# 51721300-5872P	5.0 - 10.0	
Clay	NJ TSRN# 51721300-5165P	1.0 - 5.0	
Calcium salt	7778-18-9	1.0 - 5.0	

1/6



Version 2.

Inhalation

REVISION DATE: 09/22/2008

Print Date 09/17/2010

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

: Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention

Flush with water for at least 15 minutes while holding eye lids apart. Get medical Eye contact

attention immediately.

Skin contact Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point

Method

Not available.

Lower explosion limit

Not available.

Upper explosion limit

Not available

Autoignition temperature

Not available.

Not available.

Extinguishing media

This product is not expected to burn under normal conditions of use Use

that which is appropriate to the surroundings.

Hazardous combustion

products

Not available

Protective equipment for

firefighters

Not applicable. Product is not expected to burn.

Fire and explosion conditions

This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.


SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling Precautions also apply to emptied containers. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

An RPITT Company 2/6 TR2103650001



Version 2.

Print Date 09/17/2010

REVISION DATE: 09/22/2008

Respiratory protection

: Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.

Hand protection

: Use suitable impervious rubber or vinyl gloves and protective apparel to reduce

exposure.

Eye protection

Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.

Skin and body protection

Prevent contact with shoes and clothing

Protective measures

Use professional judgment in the selection, care, and use Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation Washable or disposable clothing may be used. Do not take unwashed clothing home. Work clothes should be washed separately from other clothing and the washing machine rinsed thoroughly following use. Inform the launderer of the proper procedures. Store work clothes and street clothes separately to prevent contamination.

Engineering measures

: Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Portland cement	65997-15-1	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction
		OSHA PEL:	15 mg/m3	Total dust.
Crystalline Silica (Quartz)/	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable
Silica Sand		OSHA TWA:	0.3 mg/m3	Total dust
		OSHA PEL:	15 mg/m3	Total dust
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction
Clay	1332-58-7	ACGIH TWA:	2 mg/m3	Respirable fraction
		OSHA PEL:	5 mg/m3	Respirable fraction
		OSHA PEL:	15 mg/m3	Total dust
		OSHA TWA:	5 mg/m3	Respirable fraction
		OSHA TWA:	15 mg/m3	Total dust
Calcium salt	7778-18-9	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction
		OSHA PEL:	15 mg/m3	Total dust
		OSHA TWA:	15 mg/m3	Total dust
		OSHA TWA:	5 mg/m3	Respirable fraction
		ACGIH TWA:	10 mg/m3	Inhalable fraction



Version 2.

REVISION DATE: 09/22/2008

Print Date 09/17/2010

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form

: Powder

Color

: White

Odor

: None

Ηq

: Not available

Vapour pressure

: Not available.

Vapor density

: Not available.

Melting point/range

: Not available

Freezing point

: Not available

Boiling point/range

: Not available.

Water solubility

: Miscible

Specific Gravity

: 28

% Volatile Weight

: 00%

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid

: Not Applicable.

Stability

: Material is stable under normal storage, handling, and use.

Hazardous polymerization

: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method

Not regulated under RCRA. Dispose of in compliance with state and local regulations

Do not incinerate

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:

NOT REGULATED



Version 2.

Print Date 09/17/2010

REVISION DATE: 09/22/2008

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components

• None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

OSHA Hazardous Components:

Portland cement

65997-15-1

Crystalline Silica (Quartz)/ Silica Sand

14808-60-7

Clay

NJ TSRN# 51721300-5165P

Calcium salt

7778-18-9

OSHA Status: Considered

: Irritant

hazardous based on the

following criteria:

Carcinogen

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 0 g/l

exempt solvent)

VOC Method 310

: 0%

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components

: Portland cement

65997-15**-**1

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Calcium salt

7778-18-9

Penn RTK Components

: Portland cement

65997-15-1

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Stabilizer

NJ TSRN# 51721300-5872P NJ TSRN# 51721300-5165P

Clay

Calcium salt

7778-18-9

NJ RTK Components

: Portland cement

65997-15-1

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Stabilizer

NJ TSRN# 51721300-5872P

Clay

NJ TSRN# 51721300-5165P

Calcium salt

7778-18-9

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

14808-60-7

Crystalline Silica (Quartz)/ Silica Sand

TR2103650001 n RPM Company 5/6

Material Safety Data Sheet



TAMOSEAL WHITE 50# BG (STD)TAMOSEAL WHITE 50# BG (STD)

Version 2.

REVISION DATE: 09/22/2008

Print Date 09/17/2010

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	2
Flammability	0
Reactivity	0
PPE	
	İ

0 = Minimum 1 = Slight 2 = Moderate 3 = Serious

4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System