### **Zynolyte Hi-Temp Extreme Heat Enamel**



# Material Safety Data Sheet



TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol product. As per 29 CFR 1900. 1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following Aervoe aerosol products.

#### Zynolyte Hi-Temp Extreme Heat Enamel

Z630 Aluminum Z642 Machinery Grey Z635 Black Z645 White Z638 Almond

#### SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Aervoe Industries Inc.

INFORMATION PHONE: 775-782-3100 DATE REVISED: June 1, 2012 ADDRESS: 1100 Mark Circle, Gardnerville, NV 89410

EMERGENCY PHONE: 1-800-424-9300

REASON REVISED: New

## SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS	WEIGHT				LD50 SPECIES	LC50 SPECIES
COMPONENTS	PERCENT	OSHA PEL	ACGIH TLV	OTHER	& ROUTE	& ROUTE
Hydrocarbon Propellant		1000 ppm	1000 ppm		N / AV	N / AV
(CAS 68476-86-8)	30 - 60					
Acetone		1000 ppm	500 ppm		5800 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat-Inha)
(CAS 67-64-1)	15 - 40					
n-Butyl Acetate		150 ppm	150 ppm	200 ppm	N / AV	N / AV
(CAS 123-86-4)	1- 5					

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N/A applies to not available or not applicable

#### SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: N/A SPECIFIC GRAVITY (H20=1): .8 COEFFICIENT OF WATER/OIL DIST: N/A

ODOR THRESHOLD: N/A VAPOR DENSITY: Heavier than air SOLUBILITY IN WATER: N/A

EVAPORATION RATE: Faster than n-Butyl Acetate APPEARANCE AND ODOR: Opaque Liquid / Solvent Based Odor

FREEZING POINT: N/A pH: N/A

#### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: < 0° F (-18° C) METHOD USED: Estimated FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 0.7% UPPER: 13.0%

EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO., Dry Chemical, Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture due to pressure build up from extreme heat or fire.

FLAMMABILITY: Yes - Flammable aerosol under conditions of sparks, flame, or hot surfaces.

SENSITIVITY TO IMPACT: Do not puncture SENSITIVITY TO STATIC DISCHARGE: Primarily vapors

#### SECTION V - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: High temperatures

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide and Carbon Dioxide

HAZARDOUS POLYMERIZATION: Will not occur

#### SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause dizziness or nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: SKIN - May cause irritation or burning sensation.

EYES - Primary irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause irritation or burning sensation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: N/A

HEALTH HAZARDS (ACUTE AND CHRONIC): INHALATION - Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). SKIN OR EYE CONTACT - Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.

CARCINOGENICITY: None known NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

TERATOGENICITY: N/A MUTAGENICITY: N/A TOXICOLOGICALLY SYNERGISTIC PRODUCT: N/A

MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: None known

EMERGENCY AND FIRST AID PROCEDURES: INHALATION - Remove from exposure and restore breathing, seek medical attention.

SPLASH - (SKIN) Wash affected area with soap and water, remove contaminated clothing, seek medical attention if any irritation persists.

SPLASH - (EYES) Flush immediately with water for 15 minutes, seek medical attention if any irritation persists.

#### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition - Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with local state and federal regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame.

OTHER PRECAUTIONS: Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited.

#### SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Outdoors - Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator. For concentrations above the exposure limit, use a positive air supplied respirator.

VENTILATION: All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.

PROTECTIVE GLOVES: Impervious gloves (natural rubber) are recommended to prevent skin contact.

EYE PROTECTION: Safety glasses with side shields are recommended to prevent eye contact.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.

WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

#### SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.